

8360W

# DC BATTERY BACKUP CAPABLE CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Customizable advanced security and reliability.



## KEY FEATURES

**CUSTOMIZABLE OPENER**  
to Meet Homeowners' Needs

**WI-FI**  
Built In

**AUTOMATIC GARAGE DOOR LOCK CAPABLE**

BATTERY BACKUP CAPABLE

## SECURE

**AUTOMATIC GARAGE DOOR LOCK CAPABLE:** DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

**SECURITY+ 2.0®** SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

**POSILOCK®** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

**ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

**MOTION DETECTOR** LIGHTS THE WAY AUTOMATICALLY.

**THE PROTECTOR SYSTEM®** INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

## RELIABLE

**BATTERY BACKUP CAPABLE:** ENSURES GARAGE ACCESS DURING POWER OUTAGES (SOLD SEPARATELY).

**SOFT START/STOP** FOR SMOOTH OPERATION.

**DC MOTOR** IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

**CHAIN DRIVE SYSTEM** FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

**WARRANTY** LIFETIME MOTOR, 1-YEAR PARTS AND ACCESSORIES.

## SMART

**BUILT-IN WI-FI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.

**FREE MyQ MOBILE APP** SO USERS KNOW THEIR HOME IS SECURE.

**REAL-TIME ALERTS** INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

**MONITOR AND CONTROL** THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

## INCLUDED ACCESSORIES:

**MOTION DETECTING CONTROL PANEL**  
Activates the opener's lights automatically.



886LMW

**3-BUTTON REMOTE CONTROL**  
Operates up to 3 openers or MyQ Light Accessories.



893LM

## POWERFUL ADD-ONS:

**BATTERY BACKUP CAPABLE**  
Powers up the opener when the power's out.



485LM

**AUTOMATIC GARAGE DOOR LOCK CAPABLE**  
Deadbolts the garage door automatically every time it closes.



841LM

**REMOTE LIGHT CONTROL**  
Plug in any lamp to this device to control it with a smartphone or garage remote.



825LM

**MINI UNIVERSAL REMOTE CONTROL**  
Compact and portable to provide quick, easy garage access.



374UT

**WIRELESS KEYLESS ENTRY**  
Provides convenient, secure access from outside the garage with a 4-digit PIN.



877LM

## PRODUCT GUIDE 8360W

DC BATTERY BACKUP CAPABLE CHAIN DRIVE WI-FI GARAGE DOOR OPENER

**LiftMaster®**

**8360W**

# MASTERFUL ENGINEERING.

DC BATTERY BACKUP CAPABLE  
CHAIN DRIVE WI-FI®  
GARAGE DOOR OPENER

## MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection

## POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

## MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)

7.5"



19"

10.5"

## DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

8"

Per second for door to move upward

## SPEED

6.5"

Per second for door to move downward

## STANDARD SPECS.

### SECURITY

#### SECURITY+ 2.0®

##### RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -30°F to 150°F

##### 3-Button Remote Control (893LM)

- Remote Control: 310, 315 and 390 MHz Tri-Band\*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

\*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

##### ENCRYPTED CONTROLS

##### Motion Detecting Control Panel (886LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

### SMART

#### MyQ® RADIO

902-928 MHz  
50-Channel FHSS  
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

#### HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

### ELECTRICAL

#### LIGHTING



- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

## SHIPPING.

### SHIPPING WEIGHT

(in lbs.)

18  
HEAD20  
RAIL4  
BATTERY  
BACKUP  
(OPTIONAL)3  
AUTOMATIC  
GARAGE  
DOOR LOCK  
(OPTIONAL)

### CARTONS (4)

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head (8360W)
- Motion Detecting Control Panel (886LMW)
- 3-Button Remote Control (893LM)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel Chain T-Rail

CARTON 3 (OPTIONAL): 5.31" x 4.63" x 5.13"

- Battery (485LM)

CARTON 4 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock (841LM)

## SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation†
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices



© 2017 LiftMaster All Rights Reserved  
300 Windsor Drive, Oak Brook, IL 60523  
LiftMaster.com

Wi-Fi® is a registered trademark of Wi-Fi Alliance

UL and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved.

HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation  
LMGDENPG8360A 0617

† Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.

**LiftMaster®**