

	Sectional Aluminum				Energy Efficient Polyurethane Insulated			Polystyrene Insulated			Ribbed Panel								
	MultiView Modern 3582	Full View Heavy-Duty 3552	Full View Medium-Duty 3502	Full View Extra Heavy-Duty 2042	Heavy-Duty 2742B	Heavy-Duty 2742C	Medium-Duty 2741	Heavy-Duty 2432	Medium-Duty 2732	Medium-Duty 2731	20-gauge 2002	20-gauge 2012	20-gauge 2022	24-gauge 2402	24-gauge 2412	24-gauge 2422	Nom. 24-ga 2502	Nom. 24-ga 2512	Nom. 24-ga 2522
EXTERIOR PANEL DESIGN																			
Flush				•						•									
Deep Ribbed											•	•	•	•	•	•	•	•	•
Pencil Groove					•	•	•	•	•	•									
Stile and Rail	•	•	•																
Aluminum Sections	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
EXTERIOR PANEL TEXTURE																			
Smooth	•	•	•								•	•	•	•	•	•	•	•	•
Stucco Embossment				•	•	•	•	•	•	•									
Woodgrain Embossment																			•
INTERIOR PANEL TEXTURE																			
Smooth												•	•	•	•	•	•	•	•
Stucco Embossment				•	•	•	•	•	•	•									
CONSTRUCTION LAYERS																			
Steel + Insulation + Steel				•	•	•	•	•	•	•									•
Steel + Insulation												•	•	•	•	•	•	•	•
Steel											•	•	•	•	•	•	•	•	•
Extruded Aluminum	•	•	•																
MINIMUM STANDARD WIDTH	2' 0"	2' 0"	2' 0"	5' 0"	5' 0"	5' 0"	5' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"
MAXIMUM STANDARD WIDTH	20' 2"	24' 2"	12' 2"	40' 2"	40' 2"	40' 2"	18' 2"	24' 2"	24' 2"	18' 2"	26' 2"	26' 2"	26' 2"	30' 2"	30' 2"	30' 2"	20' 2"	20' 2"	20' 2"
MAXIMUM STANDARD HEIGHT	20' 1"	20' 1"	12' 1"	26' 1"	26' 1"	26' 1"	14' 1"	26' 1"	26' 1"	14' 1"	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	14' 1"	14' 1"	14' 1"
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)
INSULATION¹				Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polystyrene	Polystyrene	Polystyrene									
R-VALUE				19.4 ²	19.4 ²	19.4 ²	14.5 ³	9.4 ³	9.4 ³	6.7 ³									
U-VALUE				0.052	0.052	0.052	0.069	0.106	0.106	0.149									
STEEL THICKNESS (Exterior/Interior)				20/27 ga	27/27 ga	27/27 ga	27/27 ga	24/27 ga	27/27 ga	27/27 ga	20 ga	20 ga	20/25 ga	24 ga	24 ga	24/25 ga	Nominal 24 ga	Nominal 24 ga	Nominal 24/25 ga
END STILE				20 ga (16 ga optional)	20 ga (16 ga optional)	20 ga (16 ga optional)	20 ga	20 ga	20 ga	20 ga	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)
CENTER STILE																			
HINGE REINFORCEMENT				20 ga continuous strip	20 ga backer plate	20 ga continuous strip	20 ga backer plate	20 ga plate	20 ga plate	20 ga plate									
BOTTOM WEATHER SEAL																			
Aluminum Retainer	•	•	•					•	•	•	•	•	•	•	•	•	•	•	•
Dual Contact EPDM Rubber				•	•	•	•	•	•	•									
TOUNGE AND GROOVE JOINT	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WINDOW OPTIONS																			
24" x 6"				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
24" x 12"				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
26" x 13"				•	•	•	•	•	•	•									
21" x 13"																			•
41" x 13"																			•
PASS DOOR				•	•	•													
STEEL EXTERIOR COLORS																			
True White / Commercial White				TW	TW	TW	TW	TW	TW	TW	WH	WH	WH	WH	WH	WH	WH	WH	WH
Almond																			•
Wicker Tan																			•
Sandtone					•	•		•	•	•									•
Commercial Gray					•	•		•	•	•									•
Commercial Brown					•	•		•	•	•									•
Commercial Black*																			•
Amarr Color Zone*				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
HIGH CYCLE SPRINGS TO 100K	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WIND LOAD⁴ AVAILABLE	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WARRANTY⁵																			
Paint Finish	5 Years ⁶	5 Years ⁶	5 Years ⁶	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years
Workmanship/Hardware	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.

³ Calculated door section R-value.

⁵ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

*Price upcharge applies.

² Amarr 2042 and 2742 R-value tested and verified in accordance to ASTM 518 by an independent lab.

⁴ It is your responsibility to make sure your door meets local building codes.

⁶ PVDF (Kynar) and powder coat finish warranty.